

Tanged Metal Reinforced Graphite Gasket

Code: KXT1010



Description

Gaskets made by 98% pure exfoliated graphite reinforced a central layer of 0.1mm thickness tanged stainless steel. The graphite is compressed without the use of adhesives.



Item no.:KXT1010

Graphite Gasket Reinforced with Tanged metal insertion
Item no.: KXT1010

- * Tough and versatile composite for high pressures.
- * Strong composite construction without adhesives.
- * Extra strength for ease of handing and fitting.
- * With or without eyelets.

Prime Features

- * Exceptional resistance to blow-out and crushing.
- * Tough and versatile composite for high pressures.
- * Strong composite construction with or without eyelets.

Specification

- > Density: 1.0g/cm³
- > Compressibility (ASTM F36A): 15~35%
- > Recovery (ASTM F36A): \geq 20%
- > Pressure: 200bar
- > Temperature: -240~+550 oC
- > PH: 0~14

Dimension

ASME B 16.21, DIN2690, And according to your requirements.

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:sales@seal-china.com,kaxite@seal-china.com